




'Basic' ball valves

Plain/threaded outlet - PTFE - Basic System ITEM 212

REFERENCE	DESCRIPTION	Net weight	Volumen (m ³)	Gross weight	Unidades lote
1011160	PTFE BALL VALVE SOLV. S./FEM. THR. 20-1/2"	0.15	0.015532	6.24	40
1011161	PTFE BALL VALVE SOLV. S./FEM. THR. 25-3/4"	0.198	0.022435	8.46	40
1011162	PTFE BALL VALVE SOLV. S./FEM. THR. 32-1"	0.339	0.031294	10.73	30
1011163	PTFE BALL VALVE SOLV. S./FEM. THR. 40-1 1/4"	0.61535	0.031294	12.88	20
1011164	PTFE BALL VALVE SOLV. S./FEM. THR. 50-1 1/2"	0.8616	0.031294	13.497	15
1011165	PTFE BALL VALVE SOLV. S./FEM. THR. 63-2"	1.38258	0.036816	14.375	10
1011166	PTFE BALL VALVE SOLV. S./FEM. THR. 75-2 1/2"	2.67	0.031294	11.24	4
1011167	PTFE BALL VALVE SOLV. S./FEM. THR. 90-3"	4.38115	0.022435	9.25	2
1011168	PTFE BALL VALVE SOLV. S./FEM. THR. 110-4"	5.99	0.044603	12.82	2





ITEM 212 | Plain/threaded outlet - PTFE - Basic System

C??DIGO	f -r	DN	PESO (g)	A	B	C	D	E	F	G	PN	TIPO ROSCA
11160	20-1/2"	15	150	89	52	16	78	92	47	17	PN16	BSP
11161	25-3/4"	20	198	99	59	19	84	92	51	20	PN16	BSP
11162	32-1"	25	339	119	70	23	97	138	66	23	PN16	BSP
11163	40-1 1/4"	32	572	133	84	25	128	160	72	26	PN16	BSP
11164	50-1 1/2"	40	861	151	99	31	142	169	77	33	PN16	BSP
11165	63-2"	50	1382	167	121	38	165	188	90	29	PN16	BSP
11166	75-2 1/2"	65	2670	210	151	45	222	281	121	33	PN10	BSP
11167	90-3"	80	4381	245	175	51	244	301	141	36	PN10	BSP
11168	110-4"	100	5990	288	210	61	307	426	155	42	PN10	BSP



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es



Product Documents



Product Certificates



Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es