



'basic' bi-directional ball valve

PTFE male solvent socket - female solvent socket outlet ITEM 786



REFERENCE	DESCRIPTION	Net weight	Volumen (m ³)	Gross weight	Unidades lote
111D110	V.BID.S/ENC-ENC MACHO 20 PTFE	0.165	0.01553	6.9267	40
111D111	V.BID.S/ENC-ENC MACHO 25 PTFE	0.21	0.022435	8.8877	40
111D112	V.BID.S/ENC-ENC MACHO 32 PTFE	0.353	0.03129	8.163	30
111D113	V.BID.S/ENC-ENC MACHO 40 PTFE	0.606	0.03129	12.693	20
111D114	PTFE BIDIR.BASIC BALL VAL. MALE-FEMALE -SS -50	0.8704	0.03129	13.629	15
111D115	PTFE BIDIR.BASIC BALL VAL. MALE-FEMALE -SS -63	1.444	0.03682	14.9892	10



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62




tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es



ITEM 786 | PTFE male solvent socket - female solvent socket outlet

CÓDIGO	f	PESO (g)	DN	A	B	C	D	E	F	PN	MEDIDA
11D110	20	153	15	95	55	16	74	80	44	PN16	MÉTRICO
11D111	25	193	20	103	62	19	80	80	49	PN16	MÉTRICO
11D112	32	322	25	132	72	23	103	101	66	PN16	MÉTRICO
11D113	40	556	32	143	88	25	125	130	71	PN16	MÉTRICO
11D114	50	810	40	165	103	31	138	130	75	PN16	MÉTRICO
11D115	63	1263	50	194	120	38	177	170	89	PN16	MÉTRICO



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es



Product Documents



Product Certificates

Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es